BIZERBE

BIZERBA | MEAT AND BONE SAW





** COMPACT TABLE-TOP VERSION MADE OF STAINLESS STEEL.



BIZERBA _balanced information

→ WHAT DO YOU NEED FOR YOUR

CUTTING AND PORTIONING APPLICATIONS?

→ Top quality all round

The FK 23 meat and bone saw is a solid stainless steel machine finished to superior quality standards. The FK 23 is ideally suited for butchers, pre-processing rooms and canteen kitchens for cutting and portioning operations involving fresh and frozen meat, marrow and long bones. Using the FK 23 could not be simpler. The design of this attractive table-top saw is based on the latest research into modern and efficient working methods. The FK 23 features approval according to EC Machinery Directive 89/392/EEC for safety and hygiene and features a special certificate of conformity. The unit comes equipped as standard with:

- Integral motor overload protection and restart lockout;
- Motor brake; Improved band and saw wheel cleaner

system, easy to remove for cleaning; • Stainless steel saw wheels, can be removed from above: • Detachable feed device combined with height-adjustable protective rail and saw blade guide; • Thickness adjustable between 10 and 190 mm;


- Quick-action saw band tensioner via turn-handle-operated lock, combined with automatic tensioning/release of the band and saw wheel cleaner system; • Power switch integrated in membrane keypad (including indicator light); • Effortless cleaning by means of enclosed, large-area design.
 - → Optional equipment (additional charge)
- Large-size table (810 x 530 mm); Mounting stand;
- Saw bands

THE MAIN TECHNICAL SPECIFICATIONS



Current type	Voltage*)	Frequency	Amperage	Power consumption
	V	Hz	Α	kW
→ 3-phase AC:	230/400	50	2,5	1,2

→ Dimensions in mm:



- → Saw Band speed: approx. 17 m/sec.
- 1760x15x0,45 mm → Saw Band length:
- → Commodity height: max. 251 mm
- → Commodity width: min./max. 10–190 mm
- → Wheel diameter: 220 mm
- → Weight: gross weight 64,0 kg
- → Protection class: IP 55
- → Installation area: (width x depth) 360 x 350 mm
- → Outside

dimensions:

- (widthxdepthxheight) 520x580x857 mm
- \rightarrow Box dimensions: (width x depth x height) 650x590x910 mm

EFFICIENT OPERATION AND SIMPLE HANDLING. BIZERBA FK 23.











^{*)} Various voltages available depending on country-specific requirements Special details available on request